

NEW

HardwaxOil & HardwaxOil Nature

Layer-building hard wax oil

Natural look and velvety feel with excellent resistance

HardwaxOil accentuates the beauty and character of wood. Whether you are looking to create an oiled appearance or a raw wood look, HardwaxOil forms a resistant, anti-slip layer which reliably wards off moisture and dirt. It is based on modern raw materials with no harmful oximes or cobalt. Particularly safe to use – thanks to optimum application properties!



Why end customers are impressed by HardwaxOil:

- No oximes or cobalt
- Natural full-bodied look
- Silky smooth feel
- Dirt resistant and easy to clean
- Increased anti-slip properties
- Suitable for children's toys

Why contractors are excited about HardwaxOil:

- Oxime- and cobalt-free
- Smooth and full-bodied look
- Suitable for partial improvements
- Safe and particularly easy to apply
- Fast drying
- Certified anti-slip properties in accordance with DIN EN 16165:2021-12 for work areas (R10)
- Suitable for children's toys in accordance with DIN EN 71-3

Special features

HardwaxOil is based on a modern formulation with no harmful oximes or cobalt. It also has excellent application properties. HardwaxOil combines the natural, full-bodied look and velvety feel of an oil with a high resistance and dirt-repellent properties almost comparable to a finish.

Range of use

Suitable for hardwood floors and cork floors in low to normal-stress areas and even in high-traffic areas with regular care. Can be used on almost all European wood varieties and exotic wood types. You will find more information at www.loba.de/int_en/downloads under Range of use.

HardwaxOil



Roller application for wood and cork floors:

- Apply a thin even coating of HardwaxOil using the LOBA microfibre oil roller 60 – 80 or LOBA oil brush (approx. 40 – 60 ml/m² | 20 m²/l).
- Drying time of at least 8 hours, max. 24 hours.
- Perform intermediate sanding using LOBASAND GridPad fitted with a LOBASAND Hook & Loop strip and remove all dust.
- Apply a thin even coating of HardwaxOil using the LOBA microfibre oil roller 60 – 80 or LOBA oil brush (approx. 40 – 60 ml/m² | 20 m²/l).
- For highly absorbent surfaces, an additional roller application may be required after intermediate sanding with LOBASAND GridPad fitted with a LOBASAND Hook & Loop strip to achieve full homogeneous coverage.

AVAILABLE IN	ARTICLE NO.
satin	
750 ml	10509-000003-13-000
2,5 l	10509-000003-18-000
10 l	10509-000003-32-000
extra-matte	
750 ml	10509-000004-13-000
2,5 l	10509-000004-18-000
10 l	10509-000004-32-000

HardwaxOil Nature



Our HardwaxOil Nature gives an impressive untreated raw wood look. Its special composition reduces grain accentuation typically produced by oil. For hardwood floors.

Spatula and roller application:

- Carefully apply HardwaxOil Nature in sections using a LOBA finishing spatula (approx. 20 ml/m² | 50 m²/l).
- Smooth out immediately using a single-disc machine fitted with a beige LOBASAND SpecialPad.
- Drying time of at least 8 hours, max. 24 hours.
- Apply a thin even coating of HardwaxOil Nature using the LOBA microfibre oil roller 60 – 80 (approx. 40 – 60 ml/m² | 20 m²/l).
- For highly absorbent surfaces, an additional roller application may be required after intermediate sanding with LOBASAND GridPad fitted with a LOBASAND Hook & Loop strip to achieve full homogeneous coverage.

AVAILABLE IN	ARTICLE NO.
750 ml	10509-000009-13-000
2,5 l	10509-000009-18-000

Please observe the detailed technical information, processing instructions and recommended finishes.

More information:



HardwaxOil



HardwaxOil Nature

LOBA GmbH & Co. KG

Leonberger Str. 56–62 | 71254 Ditzingen | Germany | Tel.: +49 7156 357-0 | Fax: +49 7156 357-211 | E-mail: service@loba.de | www.loba.de