



2K UltraElastic | Resilient Floors

Perfect for the renovation. For a floor that looks like **new**.



2K UltraElastic restores the original beauty of the resilient floor. The highly durable protective film closes open joints and enables easy and efficient cleaning.

2K UltraElastic inspires

- Extends the life of the floor after the renovation with 2K UltraElastic the resilient floor covering looks like NEW again.
- The 2K waterbased polyurethane formula offers excellent chemical and abrasion resistance.
- The highly durable protective film closes open joints and makes cleaning easy and efficient.
- The **extramatt** finish reduces light reflection on the surface.
- Anti-slip function for increased safety (assessment group R9 | BGR 181).

Perfect results - made easy with the LOBA system

🚺 Stripping

LOBACARE[®] CareRemover 1 : 4 LOBATOOL SpecialPad green | lightly soiled LOBATOOL ScrubberPad | heavily soiled 2 Neutralising (machine) brushing



8 Finishing

1 x for normal to heavy wear 2 x for heavy to extremely heavy wear

- Easy to use formulation **mix and start immediately**.
- Lap-free application.
- Seals the joints, protects the substrate.

LOBADUR[®] 2K UltraElastic – range of use

Especially developed for the renovation of linoleum, PVC, CV and LVT floor covering. Also suitable for non-vulcanised rubber granules (EPDM rubber).

Ideal for floors with **heavy use and increased demands on slip resistance** in public and private areas, e.g. health centres, retirement homes, yoga studios etc.



Hospital, Robert-Bosch-Krankenhaus, Stuttgart

Your service partner.

LOBA is always at your side and ensures your success with advice and action. Our experienced application specialists will advise you individually on your projects and our competent service team is quickly on site if you need practical support directly on site. So you play it safe right from the start and know who you can rely on at all times.



Visit our download area for technical information, set-up recommendations and application videos.

Any further questions? Feel free to contact us, we are happy to assist you at any time! +49-7156-357-0 | service@loba.de

BGR 181

Technical Data Sheet