

LOBADUR® 

2K Contact

2K water-based bonding agent

Dust-free renovation system for prefinished floors

Gives your floor a fresh look without sanding!

LOBADUR® 2K Contact is a unique system that enables dust-free renovation of prefinished floors. It was developed in collaboration with a global leader in UV finishing technology and has been tested on countless brands of factory finished floors. The system gives prefinished wood and cork floors a fresh appearance and new durability.



Why end users are convinced of 2K Contact:

- The most convenient way of recoating – no sanding, no noise, no dust
- The original structure and the top layer of the floor remains unchanged
- Water-based technology and low VOC ensures a minimum of emissions and a low environmental footprint
- Extends the floor's lifetime – great contribution to sustainability
- Time saving and economical renovation

Why contractors are enthusiastic about 2K Contact:

- Easy to use – ensures perfect adhesion of the recoat
- No sanding machine needed
- High coverage provides great value
- The safest way to recoat textured, hand scraped and distressed surfaces
- Can help to correct surface scratches

Special feature

LOBADUR® 2K Contact is the only system available that provides a true chemical bond between the original finish and the recoat. Excellent adhesion is perfectly ensured!

Range of use

Suitable for factory applied UV-finished wood and cork floors.

Application

Renovation

- Basic cleaning with single disc machine, LOBATool SpecialPad green and LOBACARE® CareRemover 1:4
- Remove dirt with a water vacuum cleaner and neutralize with clear water or use a scrubbing machine
- Allow to dry sufficiently
- Apply WS 2K Contact in an even, thin coat
- After tack-free drying (approx. 2-4 hours), coat with LOBADUR 2K Supra A.T. or LOBADUR 2K Supra (available in extra matte, satin or semi-gloss – not suitable for glossy sheen)

Newly installed surface

Consult LOBA technical department to check suitability for recoating. If necessary establish test area and perform adhesion test.

- Coverage: 500-600 square feet per mixed container

LO-FI-008

Available in 1 Qt.

US Regulatory VOC < 240 g/l



LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

Do you have any questions? Do not hesitate to contact us:

Please consider the detailed technical information, application advices and set-up recommendations.

Technical Information



Loba-Wakol LLC

Proudly located in North Carolina | Phone: (704) 527-5919 | E-Mail: info@loba-wakol.com | www.loba-wakol.com