

DeckRefresh



Cleans and maintains your wood deck in one wipe!

Water-based wipe care for outdoor areas. Wipe care product with environmental factor: LOBA DeckRefresh makes your deck shine silky again and is based on purely natural ingredients. Our freshness cure for your favorite place - in harmony with nature!

- Thorough, gentle wipe care
- Gives the surface a silky sheen
- Easy and safe application
- No remover necessary due to a self-emulsifying formula
- Suitable for oiled and finished wood surfaces in outdoor areas

Recommended use:

Suitable for the maintenance of WPC and oiled wood.

Product data

ART.-NO.	ITEM-#			
10711	LO-FI-304	2.5l	6	216

pH

7.2

Contents

< 5% non-ionic surfactants, LIMONENE, perfumes, SODIUM PYRITHIONE, METHYLCHLOROISOTHIAZOLINONE AND METHYLISOTHIAZOLINONE (3:1), BENZISOTHIAZOLINONE

Storage and transportation

Shelf life: 36 months in unopened containers.
Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

Information for Use

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.

APPLICATION TOOL

LOBA Mop

COVERAGE

For maintenance cleaning and care cleaning, add 50ml - 1l into 10l of water (mixing ratio of 1:10-1:200). 30-550 square feet per 2.5l container.

DRYING TIME

- approx. 30 min.

Maintenance care:

For weekly cleaning and care, add approx. 50-100ml (mixing ratio of 1:100-1:200) of LOBA DeckRefresh to 10l of water. Wipe the patio deck using LOBA Mop and the cleaning solution. Allow residual moisture to dry.

Care:

Remove loose dirt mechanically. Clean surface with LOBA Deck-Cleaner according to technical information. Add 1l LOBA Deck-Refresh to 10l (mixing ratio of 1:10) water and clean the surface evenly with a LOBA mop. Do not walk on the surface during drying.

Note for wooden decks that are severely worn:

LOBA DeckRefresh is only suitable for wooden decks with a largely intact finish coat / oil impregnation and is only to be used for refreshing between the annual renovation cycles. For re-finishing or re-oiling the surface we recommend LOBA DeckOil or LOBA DeckFinish Color.

COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

General guidelines

Cleaning of tools: Clean tools with solvents such as brush cleaner.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.