DeckCleaner





From nature - for nature! Powerful herbal based cleaning for your outdoor area

Maintenance cleaner for outdoor areas LOBA DeckCleaner is a gentle, vegetable based, and biodegradable cleaner that even removes stubborn dirt.

- Can be used on horizontal and vertical surfaces and outdoor furniture, does not drip
- Very productive
- Suitable for oiled or finished wood and WPC

Recommended use:

Suitable for cleaning WPC, oiled and finished wood.

Product data

ARTNO.	ITEM-#		\subseteq	5
10731	LO-FI-305	2.51	6	216

pH 9.6

Contents 5 - 15% soap

Storage and Shelf life: 36 months in unopened

transportation containers.

Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

Information for Use

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.

APPLICATION TOOL

LOBA Mop or Scrubber.

COVERAGE

Mix at a ratio of DeckCleaner: water between 1:40 and 1:200 (50-250ml DeckCleaner: 10L water). 110-540 square feet per 2.5l container.

APPLICATION:

For regular cleaning and before applying DeckRefresh and WPC Refresh. Depending on the degree of soiling, mix at a ratio of DeckCleaner: water between 1:40 and 1:200. Apply cleaning solution to the surface and remove after a short exposure time with the LOBA mop. In case of grooved terrace decks or heavy soiling, treat the surface with a scrubbing brush. If necessary, repeat the cleaning process. Then rinse off any cleaning agent residues with clear water.

Information for Use

In case of high application concentration, a slight leaching may occur on oiled surfaces. In this case, we recommend a subsequent application of WPC Refresh on these surfaces after drying overnight to restore the impregnation. High application concentrations can lead to leaching of the oiled surfaces. To restore the impregnation, after drying overnight, LOBA WPC Refresh (light impregnating effect) or LOBA DeckOil (strong impregnating

effect) can be applied.

COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

General guidelines

Cleaning of tools: Clean tools with solvents such as brush cleaner.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.