

# DeckDegrayer



## Back to Start: Undo the weathering of your wood!

Special cleaner for wooden surfaces in outdoor areas. Renovation without sanding! LOBA DeckDegrayer brings back the natural color of wood. Use the biodegradable special cleaner for your deck, outdoor furniture and wooden objects.

- Ideal degreasing preparation prior to surface treatment
- Easy and safe application
- Can be used on horizontal and vertical surfaces and outdoor furniture, does not drip
- No sanding necessary
- Applicable for all wood species

## Recommended use:

Suitable for use on exterior wooden surfaces.

## Product data

ART.-NO.	ITEM-#			
10741	LO-FI-306	2.5l	6	216

### pH

2.7

### Contents

< 5% non-ionic surfactants,  
METHYLCHLOROISOTHIAZOLINONE AND  
METHYLISOTHIAZOLINONE (3:1)

### Storage and transportation

Shelf life: 36 months in unopened containers.  
Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

## Information for Use

- For professional use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Transfer material to a LOBA coating bucket before applying.
- Optimum climate conditions are 60°F to 80°F (15°C to 25°C), relative humidity 40% to 75%, material temperature 60°F to 80°F (15°C to 25°C).
- Do not apply to surfaces exposed to hot or strong sunlight, as the applied coating may dry too quickly. Do not apply if rain is expected within 3 hours of application.
- If in doubt, create a test area to determine compatibility, adhesion and appearance. The results may vary depending on the type of wood, especially with oily, resinous and chemically pre-treated woods.
- Avoid drips falling on the surface, smooth out any drips immediately with a brush.
- **WARNING!** If you scrape, sand, or remove old paint from wood floors, you may release lead dust. Follow local and/or federal requirements for lead removal. Before you start, find out how to protect yourself and others by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### APPLICATION TOOL

Brush or LOBA Oilbrush

### COVERAGE

140-200 square feet per 2.5l unit. Determine the exact coverage with a test application.

### DRYING TIME

- approx. 12 hours.

### THREE AREAS OF APPLICATION, ONE PROCEDURE.

#### Degrayer old oiled decks

- The special formulation allows you to remove wood graying.

#### Clean and prepare old finished deck for re-finishing

- Optimal preparation for secure adhesion of the subsequent finish layer.

#### Newly laid deck, open pores, wash out wood ingredients from surface

- Woods with a high content of wood ingredients, especially coniferous and exotic woods, tend to accumulate on the surface of the wood, e.g. teak that has not been freshly sanded even feels oily.
- In order to achieve an optimal bond between our products and the wood, these wood ingredients, resins and oils, must be washed off the surface. This opens the pores of the wood surface as well and the products can be better absorbed.

### APPLICATION

- Remove loose dirt with broom in advance.
- Moisten the surface with water first to prevent LOBA Degrayer from drying too quickly.
- Apply LOBA DeckDegrayer undiluted with a brush or LOBA oil brush to the wood to be cleaned.
- Allow material to react for approx. 10 minutes.
- To prepare the surface, we recommend a cleaning machine suitable for wooden decks (automatic suction and scrubbing machine, high-pressure cleaner with corresponding attachment, etc.). Alternatively, use a scrubber or brush to work the surface along the wood grain.
- Then rinse the entire surface with clear water or spray it with a garden hose. In case of very stubborn soiling, repeat the treatment or allow LOBA DeckDegrayer to work for a longer time.
- After drying, optionally break up wood fibers with a steel broom or disc machine and LOBASAND SuperPad green to achieve a smoother surface. Re-oil with LOBA DeckOil or coat with LOBA DeckPrepare and LOBA DeckFinish. Refer to the Technical Data Sheet of the product.

### COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

## General guidelines

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Cure Time:** The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

**Safety Precautions:** Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

**First Aid:** If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

**Special Information** The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website [www.loba-wakol.com](http://www.loba-wakol.com). You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.