



SlipResist



ADDITIVE





Additive to improve slip resistant properties. The addition of LOBA SlipResist in the final coat of finish achieves certified slip resistance. Enhances the versatility of existing LOBA water-based finishes without the need to stock a specialty finish.

- Certified slip resistance
- Will not attract dirt and debris
- Water-based technology, solvent-free
- Simple and safe application
- Maintains finish clarity

Recommended use:

Perfectly formulated for LOBA EasyFinish, LOBA 2K Duo, LOBA 2K InvisibleProtect A.T. and LOBA Supra A.T. Not recommended for gloss sheens.

Product data

ART.-NO.	ITEM-#		
11018	LO-FI-347	3 fl. oz.	15

Storage and transportation

Shelf life: 12 months in unopened containers.
Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

Information for Use

- For professional use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA guidelines.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE, AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F (13°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks, puddles, and lap marks.

MIX IN:

- Shake up LOBA SlipResist and finish.
- For 2K finishes, add LOBA SlipResist to finish and shake vigorously before adding hardener. This will make it easier to mix partial quantities if needed. Mass with additive has a storage stability of 14 days.
- Add one container of 3 fl.oz. to 1 gal. of finish.
- Attention: In order to ensure the slip resistant properties, the additive quantities must be exactly observed.
- Shake combined materials thoroughly.
- Apply 2K finish mixed with LOBA SlipResist within the specified working time. Longer stability is not guaranteed.

Information for Use

SUITABILITY:

Can be combined with approved finishes. The application properties of the finish, product compatibility and drying time remain unchanged. Please observe the technical information of the corresponding finish.

ACHIEVES SLIP RESISTANCE ACCORDING TO ASTM D 2047-17 AND DIN EN 16165:2021-12 WITH THE FOLLOWING FINISHES:

Finish	Before S.R.	With S.R.	DIN EN 16165
EasyFinish	0.67	0.79	R10
2K Duo	0.65	0.74	R10
2K InvisibleProtect	0.65	0.75	R11
2K Supra A.T.	0.73	0.79	R10

Note: To achieve an R11 surface with 2K InvisibleProtect in combination with SlipResist, a 3 coat application is required. The first coat can also be replaced by a sealer.

COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 50% RH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol’s General Terms and Conditions, including without limit its limited warranty (“Terms”). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer’s responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.