

Amberizer



ADDITIVE



Amberizer is an additive to achieve the traditional look of an aged oil modified polyurethane finish with water-based coatings.

- Adds the look of oil-based finish
- Great to touch up and repair old floors
- Convenient package and great color consistency

Recommended use:

Suitable for all LOBA Water-based finishes. For all dark wood species as well as dark-colored wood surfaces. For light wood species we recommend consultation with LOBA.

Product data

ART.-NO.	ITEM-#		
11540	LO-FI-001	3 fl. oz.	15

Storage and transportation

Shelf life: 36 months in unopened containers.
Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

Information for Use

- For professional use only!
- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA guidelines.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE, AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F (13°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks, puddles, and lap marks.

DRYING TIME

- Amberizer does not alter the dry time of the desired finish.

MIXING RATIO

Added amount 2%. One bottle to one gallon.

RECOMMENDED PROCEDURE FOR WOOD FLOORS:

- Add Amberizer only right before the application by shaking or stirring thoroughly. When using 2-component-systems
- (2K Duo, 2K Supra A.T.) add Amberizer only AFTER adding hardener to the mass!
- 1K finish mixed with LOBA Amberizer must be applied within 24 hours, 2K finishes within the indicated application time. Longer stability is not guaranteed.

Information for Use

Can be combined with all LOBA water-based finishes and sealers. The application properties of the finish, its product combinability, and the drying time remain unchanged. Refer to the Technical Data Sheet of the corresponding finish.

COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.