



Rush

satın

UV-curing 1-component water-based polyurethane finish for wooden floors. For extremely heavy wear.

Emissions

	<p>Emicode® EC1 Plus, very low emission</p>	<p>According to GEV (Community Emission Controlled Flooring Adhesives and Construction Products e.V., Düsseldorf)</p>
	<p>A+</p>	<p>According to French VOC classification</p>

Glossar

GEV Emicode

The EMICODE® symbol identifies building materials and products that emit no or very low fugitive emissions into the indoor air. The award is made by GEV, Gemeinschaft Emissionskontrollierter Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. The GEV was founded in 1997 by industrial companies to promote products that are harmless to health and the environment. External test institutes certified according to ISO 17025 test the emission behaviour of parquet varnishes. In addition, parquet lacquers with a high solvent content are not approved for testing. This means that the needs of users and residents alike are taken into account. Products marked with EMICODE® are checked regularly. www.emicode.de

DGALN

The French VOC classification classifies construction products that are permanently processed indoors according to their emissions into emission classes A+, A, B or C, where A+ stands for the best and C for the worst emission class. These construction products have had to be labelled in France since 2012.

Notes

Notice

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to special conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.