



2K Supra A.T. satin

Ceramic-reinforced water-based 2-Component polyurethane finish. For extremely heavy wear.

Emissions

 <p>Loba GmbH & Co. KG Emissionsgeprüftes Bauprodukt nach DIBt-Grundsätzen Z-157.10-2</p>	<p>Approval number Z-157.10-2</p>	<p>According to DIBt (German institute for building technology)</p>
--	---------------------------------------	---

Technical evaluation

<p>US Regulatory VOC</p>	<p>< 155 g/l</p>
--------------------------	---------------------

Glossar

DIBt

For reasons of health protection, the German Institute for Building Technology (DIBt) requires a general building supervisory approval for all building products used for the treatment and bonding of parquet on site. Certified building materials are marked with the Ü symbol. This obligation to obtain approval has been in force in Germany since 1 January 2011. In order to obtain approval, compliance with emission limits must be proven and the formulations must be disclosed to the DIBt. www.dibt.de

US Regulatory VOC

Article 1113 was adopted in September 1977. The aim of this regulation is to limit the content of volatile organic compounds (VOCs) in architectural paints. Any person who supplies, sells, offers for sale or manufactures architectural coatings for use in SCAQMD must comply with the current VOC standards.

Notes

Notice

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.